



LPG

STEEL PORTABLE



SPECIFICATIONS

MODEL/SIZE (LBS.)	4.25	11	20	30	40	43.5	60	100
HEIGHT (IN.)	11.8	16.8	17.8	23.7	29.3	32.5	44.1	48.7
HEIGHT (MM)	300	427	452	602	744	825.5	1,120	1,240
LPG CAPACITY (GAL)	1	2.6	4.7	7.1	9.4	10.3	14.2	23.6
LPG CAPACITY (LITER)	3.8	9.8	17.8	26.9	35.6	39	53.8	89.3
WATER CAPACITY (LBS.)	12	26.2	47.6	71.5	95.2	103.6	142.9	239
WATER CAPACITY (KG)	5.4	11.9	21.6	32.4	43.2	47	64.8	108.4
NOMINAL TARE WEIGHT (LBS.)	11	13.1	16.6	23.5	29.1	33.9	48.1	68
NOMINAL TARE WEIGHT (KG)	5	5.9	7.5	10.6	13.2	15.4	21.8	30.8
CYLINDER DIAMETER (IN.)	9.1	9.1	12.3	12.3	12.3	12.3	12	14.7
CYLINDER DIAMETER (MM)	231	231	312	312	312	312	305	373
CYLINDER VOLUME (CU. IN.)	332	725	1,318	1,980	2,635	2,868	3,955	6,616
CYLINDER VOLUME (LITER)	5.4	11.9	21.6	32.4	43.2	47	64.8	108.4
COLLAR DIAMETER (IN.)	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
COLLAR DIAMETER (MM)	165	165	165	165	165	165	165	165
COLLAR HEIGHT (IN.)	4	4	4	4	4	5.1	5.1	5.1
COLLAR HEIGHT (MM)	102	102	102	102	102	130	130	130
FOOTRING DIAMETER (IN.)	9.1	7.8	7.8	7.8	7.8	12	12	14.5
FOOTRING DIAMETER (MM)	231	198	198	198	198	305	305	368
HORIZONTAL	N/A	N/A	Available	Available	Available	N/A	N/A	N/A
STANDARD SPECIFICATION	DOT-4BA-240	DOT-4BA-240	DOT-4BA-240	DOT-4BA-240	DOT-4BA-240	DOT-4BA-240	DOT-4BW-260	DOT-4BW-240

All dimensions are approximate.